

CIRCUIT-LOCK® NEMA 4X Enclosures with Switch and Accessories

Ideal for use in environments where washdown is necessary, i.e. food processing, laboratories, etc.



Amp	Poles	HP Rating				Catalogue Numbers
		120V AC	240V AC	480V AC	600V AC	
30	3	3	7.5	15	20	HBL13S33D
60	3	—	10	25	30	HBL16S63D
Finger Guard option for 30A switch						HBLFG30
NO/NC auxiliary contact, 10A 120/250 V AC for 30 and 60 Amp switches						HBLAUX

NEMA 4X Non-Metallic Switched Enclosure, Unfused

Used primarily in heavy wash-down and corrosive environments.



Description	HP Rating				Catalogue Numbers
	120V AC	240V AC	480V AC	600V AC	
30A Disconnect switch	1	7.5	15	15	HBLDS3
30A Disconnect with Jog Switch	1	7.5	15	15	HBLDS3J
30A Disconnect with NO+NC Aux Contact and Jog Switch	1	7.5	15	15	HBLDS3ACJ
30A Disconnect with NO Break Before Main Aux Contact and Jog Switch	1	7.5	15	15	HBLDS3VFDJ
30A Disconnect switch w/aux. contact	1	7.5	15	15	HBLDS3AC
60A Disconnect Switch	7.5	30	50	50	HBLDS6
60A Disconnect switch with Jog Switch	7.5	30	50	50	HBLDS6J
60A Disconnect switch w/aux. contact	7.5	30	50	50	HBLDS6AC
100A Disconnect Switch	7.5	30	50	50	HBLDS10
100A Disconnect switch w/aux. contact	7.5	30	50	50	HBLDS10AC
Aux. contact, break after break	—	—	—	—	HBLAC1
Aux. contact, break before break	—	—	—	—	HBLAC2
Ground block (30A switch)	—	—	—	—	HBL30RGB
Ground block (60A and 100A switch)	—	—	—	—	HBL60100RGB
Neutral block (30A switch)	—	—	—	—	HBL30RNB
Neutral block (60A switch)	—	—	—	—	HBL60RNB
Neutral block (100A switch)	—	—	—	—	HBL100RNB
Replacement 30A switch	1	7.5	15	15	HBLDS3RS
Replacement 60A and 100A switch	7.5	30	50	50	HBLDS60100RS
30A Disconnect switch - fused	2	7.5	15	20	FDS30
60A Disconnect switch - fused	3	15	30	40	FDS60
Aux. contact, norm. open, A600 pilot duty	—	—	—	—	ACFSNO
Aux. contact, norm. closed, A600 pilot duty	—	—	—	—	ACFSNC

600V AC Manual Motor Controllers

For use in almost any industrial environment.



Amp	Poles	Toggle Type	Wire	HP Rating				Catalogue Numbers
				120V AC	240V AC	480V AC	600V AC	
30	2	Standard	—	2	5	10	15	HBL7832D
30	2	Short	—	2	5	10	15	HBL7832DS
30	3	Standard	—	3	7.5	15	20	HBL7810D
30	3	Short	—	3	7.5	15	20	HBL7810DS
40	2	Standard	—	2	5	10	15	HBL7842D
40	3	Standard	—	3	7.5	15	20	HBL7843D
50	2	Standard	—	2	5	10	15	HBL7852D
50	3	Standard	—	3	7.5	15	25	HBL7853D
60	2	Standard	—	—	10	15	20	HBL7862D
60	3	Standard	—	—	10	25	30	HBL7863D
60	2	Standard	Front	—	10	15	20	HBL7862FWD
60	3	Standard	Front	—	10	25	30	HBL7863FWD
85	2	Standard	—	—	10	15	20	HBL7882D
85	3	Standard	—	—	10	25	40	HBL7883D
Finger Guards (red) for use with 30, 40 and 50A switches							(set).	HBLFG30

Labelless Circuit-Lock® NEMA 4X, 12 NSF Stainless Steel Enclosures with Switch, Unfused

Square Top - Ideal for hygiene applications in food and beverage processing.



Amp	Poles	Enclosure Material	HP Rating				Catalogue Numbers
			120V AC	240V AC	480V AC	600V AC	
30	3	Stainless Steel	1	7.5	15	15	HBLDS3SS
30	3	Stainless Steel	1	7.5	15	15	HBLDS3SSJ
30	3	Stainless Steel	1	7.5	15	15	HBLDS3SSAC
30	3	Stainless Steel	1	7.5	15	15	HBLDS3SSVFD
60	3	Stainless Steel	7.5	30	50	50	HBLDS6SS
60	3	Stainless Steel	7.5	30	50	50	HBLDS6SSAC
100	3	Stainless Steel	7.5	30	50	50	HBLDS10SS
100	3	Stainless Steel	7.5	30	50	50	HBLDS10SSAC

Labelless Circuit-Lock® NEMA 4X, 12 NSF Stainless Steel Enclosures with Switch, Unfused

Sloped Top - Ideal for hygiene applications in food and beverage processing.



Amp	Poles	Enclosure Material	HP Rating				Catalogue Numbers
			120V AC	240V AC	480V AC	600V AC	
30	3	Stainless Steel	1	7.5	15	15	HBLDS3SSR
30	3	Stainless Steel	1	7.5	15	15	HBLDS3SSRJ
30	3	Stainless Steel	1	7.5	15	15	HBLDS3SSRAC
30	3	Stainless Steel	1	7.5	15	15	HBLDS3SSRVFD
60	3	Stainless Steel	7.5	30	50	50	HBLDS6SSR
60	3	Stainless Steel	7.5	30	50	50	HBLDS6SSRAC
60	3	Stainless Steel	7.5	30	50	50	HBLDS6SSRVFD
100	3	Stainless Steel	7.5	30	50	50	HBLDS10SS
100	3	Stainless Steel	7.5	30	50	50	HBLDS10SSAC
100	3	Stainless Steel	7.5	30	50	50	HBLDS10SSRAC

Labelless Circuit-Lock® NEMA 4X, 12 Enclosures with Switch, Unfused

Ideal for use in harsh environments with exposure to water, chemicals, oils and frequent washdowns.



Amp	Poles	Enclosure Material	HP Rating								Catalogue Numbers
			120V AC	208-240V AC	240V 3Ø	480V AC 3Ø	600V AC 3Ø	120/208V 3ØY	277/480V 3ØY	347/600V 3ØY	
200	3	Stainless Steel	1.5	3	7.5	15	15	7.5	15	15	HBLDS20
200	3	Non-Metallic	1.5	3	7.5	15	15	7.5	15	15	HBLDS3SSRAC